



主要技术参数、性能
The Main Thchnology Performance

额定电流、电压 Rate voltage current	50mA 20VDC ~100 μ A 3V DC
接触电阻 Contact resistance	500m Ω ~1 Ω . MAX
绝缘电阻 insulated resistance	100m Ω Min 100V DC
使用湿度 Ambient humidity used	$\leq 85\%$ RH
使用温度 Operating temperature	-25 $^{\circ}$ C+80 $^{\circ}$ C
耐焊温度 Withstand Soldering temperature	245 $^{\circ}$ C $\pm 5^{\circ}$ C 3S ± 0.5 S
寿命 Life	100.000Cycles

E				
D				
C				
B				
A				
项目 ITEM	名称 DESCRIPTION	材质 MATERIAL	数量 QYT	表面处理/颜色 FINSH/COLOR

						第一视角 FIRST VIEW		名称/NAME: 检测开关 DETECTOR SWITCH	
								型号/MODEL: DS-008S	
标记 SING	处数 FREQUENCY	更改文件号 REVISION	签名 APPROVED	日期 DATE	比列 SCALE	mm	一般公差 GENERAL TOLERANCE		
设计 DESIGN		Zhaoming			单位 UNIT	mm	0.5~2	± 0.10	
审核 CHECKED		Zengyong			重量 WELGHT		2~5	± 0.15	
批准 APPROVED		Fuyunfeng					5~10	± 0.20	
							角度 ANGLE	$\pm 0.5^{\circ}$	

