


P.C.B.Layout



主要技术参数、性能  
The Main Thchnology Performance

|                                 |                                |
|---------------------------------|--------------------------------|
| 额定电流、电压<br>Rate voltage current | 12V DC,50mA                    |
| 接触电阻<br>Contact resistance      | ≤100mΩ . MAX                   |
| 操作力<br>Operating force          | 180 ± 50 gf<br>for 250 ± 50 gf |
| 耐焊规格<br>Solder Specifications   | 260°C for<br>3 Seconds         |
| 绝缘电阻<br>insulated resistance    | ≥100mΩ . MIN                   |
| 寿命<br>Endurance                 | 200,000 cycles                 |
| 使用温度<br>Service temperature     | -20°C to 70 °C                 |
| 总行程<br>TOTAL TRAVEL             | 0.25±0.1mm                     |

| E          |                   |                |           |                        |
|------------|-------------------|----------------|-----------|------------------------|
| D          |                   |                |           |                        |
| C          |                   |                |           |                        |
| B          |                   |                |           |                        |
| A          |                   |                |           |                        |
| 项目<br>ITEM | 名称<br>DESCRIPTION | 材质<br>MATERIAL | 数量<br>QYT | 表面处理/颜色<br>FINSH/COLOR |

|                    |                   |                |            |                  |                           |  |  |  |  |
|--------------------|-------------------|----------------|------------|------------------|---------------------------|--|--|--|--|
| 第一视角<br>FIRST VIEW |                   |                |            |                  |                           | 名称/NAME:<br>带灯开关<br>ILLUMINATED TACT SWITCH SERIES |  |  |  |
| 标记<br>SING         |                   |                |            |                  |                           | 型号/MODEL:<br>TS-05L                                |  |  |  |
| 处数<br>FREQUENCY    | 更改文件号<br>REVISION | 签名<br>APPROVED | 日期<br>DATE | 比列<br>SCALE      | 一般公差<br>GENERAL TOLERANCE |  |  |  |  |
| 设计 DESIGN          | Zhaoming          |                |            | 单位<br>UNIT<br>mm | 0.5~2                     | ±0.10  |  |  |  |
| 审核 CHECKED         | Zengyong          |                |            | 重量<br>WELGHT     | 2~5                       | ±0.15  |  |  |  |
| 批准 APPROVED        | Fuyunfeng         |                |            |                  | 5~10                      | ±0.20  |  |  |  |
|                    |                   |                |            |                  | 角度<br>ANGLE               | ±0.5°  |  |  |  |

